

# GMJJ2.EX28635 - Storage Containers for Extinguishing System Units - Component

## Storage Containers for Extinguishing System Units - Component

### Auto Firex LLP

Gram Dungsil Malla  
Patti Pandey Gaon  
Bhimtal  
Nainital, Uttarakhand 263136 India

EX28635

Type	Max Volume, Cu. Ft. (ltrs)	Cylinder Diameter, Inch. (mm)
Aluminium Seamless Alloy Cylinder, 135Bar ISO 7866:2012+ COR 1:2014(UN Cyl)	0.05 (1.)	3.54 (90)
Aluminium Seamless Alloy Cylinder, 190Bar ISO 7866:2012+ COR 1:2014(UN Cyl)	0.08 (2.2)	4.37 (111)
Aluminium Seamless Alloy Cylinder, 190Bar ISO 7866:2012+ COR 1:2014(UN Cyl)	0.16 (4.5)	4.37 (111)
Aluminium Seamless Alloy Cylinder, 190Bar ISO 7866:2012+ COR 1:2014(UN Cyl)	0.28 (7.8)	5.98 (152)
Aluminium Seamless Alloy Cylinder, 190Bar ISO 7866:2012+ COR 1:2014(UN Cyl)	0.38 (10.7)	5.98 (152)

Marking: Company name or identification, type designation and the Recognized Component Mark 

Tradename and or Trademark:



الشركة الدولية لأنظمة الأمن والسلامة  
Int. Security & Safety Systems Co.

Last Updated on 2022-01-07

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"